





Ls SMD5050 60 LED 3000K IP65

SKU 2149 EAN 3800230621511 VT-5050

Related products (SKUs): 2118, 2122, 2124, 2126, 2127, 2128, 2129, 2133, 2136, 2137, 2138, 2142, 2143, 2145, 2148, 2151, 2152, 2153, 2155, 2156, 2159, 2358, 2430, 2544, 2547, 2552, 2553, 2563, 2583, 2584, 2591, 2592, 3005, 2431, 2459, 2562, 23145, 23146, 212135, 212563


TECHNICAL SPECIFICATION

Power	10W	Current	0.8A/m.	Width	10mm
Luminous flux (lm)	1000 lm	Number of LEDs	60 LED/m.	Product weight	0,325
Light color	Warm white	LM / LED	14-16lm	Volume	0,0002
Color temperature	3000K	CRI	80+	Pack length	210mm
Beam angle	120°	Material	PCB	Pack width	10mm
Voltage	12V	Type	60LED/m	Pack height	260mm
SKU	SKU 2149	Dimming	TAK	Master carton	80
EAN barcode	3800230621511	IP rating	IP65	Quantity per pallet	6000
Product code	VT-5050	Cut point	Copper points on the strip indicate the cut lines.	Brand	V-TAC
Series	LED strips	Ignition time (100%)	0.001s	Warranty	2y
Energy class	F	Color consistency	<6	Certifications	CE, EMC, ROHS
Shape	LED strip	Declared intensity (cd)	318.30 Cd Max.	Efficacy (lm/W)	100 lm/W
LED module type	SMD5050	On/Off cycles	15000	Parameters	Power and luminous flux are given for 1m of product
Lifetime	>20000h	Operating conditions	-20° +45°	ETIM	ECO01959
Input voltage	12V DC	Length	5m	CN code	8539 52 00

TECHNICAL SPECIFICATION

Page 2/2

EPREL	926429
-------	--------

**Ls SMD5050 60 LED 3000K IP65**

SKU 2149 EAN 3800230621511 VT-5050

Related products (SKUs): 2118, 2122, 2124, 2126, 2127, 2128, 2129, 2133, 2136, 2137, 2138, 2142, 2143, 2145, 2148, 2151, 2152, 2153, 2155, 2156, 2159, 2358, 2430, 2544, 2547, 2552, 2553, 2563, 2583, 2584, 2591, 2592, 3005, 2431, 2459, 2562, 23145, 23146, 212135, 212563

Product description

- Flexible LED strip for voltage 12V
- The coating of the strip provides much better protection of the LED strip against moisture, water and dirt than traditional silicone. Additional double-sided tape for easier installation
- Quick and easy installation
- Extremely low energy consumption
- Create atmospheric and dynamic illuminations
- Available in a variety of colors from warm white to RGB
- IP20 and IP65 versions

GPSR Information

- Manufacturer: V-TAC Europe Ltd. Address: bul. "Rozhen" 41, 1271 Sofia, Bulgaria, office@v-tac.eu
- Importer: V-TAC Europe Ltd. Address: bul. "Rozhen" 41, 1271 Sofia, Bulgaria, office@v-tac.eu
- Distributor and importer in Poland: Led Europe Sp. z o.o. Address: ul. Starorudzka 12E 93-491 Łódź, Poland, biuro@led-europe.pl
- Documents confirming compliance of products with applicable safety standards are available on the website www.v-tac.eu. If the required documentation is not available, please contact the local distributor: biuro@led-europe.pl
- If you have any problems with the product, contact the distributor in Poland: biuro@led-europe.pl
- Country of production: China