






**40W LED 2in1 LED backlit panel light with CREE CHIP
1200*300mm 4000K**

SKU 21662516 EAN 3800170252271 VT-6147

Related products (SKUs): 6624, 6625, 6626, 216625, 216626, 2166251, 2166256, 2166261



TECHNICAL SPECIFICATION

Power	40W	Frequency	50/60Hz	Pack width	335mm
Luminous flux (lm)	4400 lm	Power factor	>0,9	Pack height	250mm
Light color	Neutral white	CRI	80+	Master carton	6
Color temperature	4000K	Material	PKW	Brand	V-TAC
Beam angle	110°	Housing color	White	Warranty	6y
Voltage	230V	Type	Frame/Recessed	Certifications	CE, EMC, ROHS
SKU	SKU 21662516	Dimming	NIE	Efficacy (lm/W)	110 lm/W
EAN barcode	3800170252271	IP rating	IP20	ETIM	EC002892
Product code	VT-6147	Ignition time (100%)	0.001s	CN code	8539 51 00
Series	Ceiling lighting	On/Off cycles	>25000	EPREL	2402783
Energy class	E	Operating conditions	-20° +45°		
Base	Integrated LED fixture	Size	1195x295x30mm		
Shape	Rectangle	Length	120cm		
LED module type	CREE LED	Product weight	2,6		
Lifetime	50000h	Volume	0,017856		
Input voltage	AC:220-240V, 50/60Hz	Pack length	1220mm		

**40W LED 2in1 LED backlit panel light with CREE CHIP
1200*300mm 4000K**

SKU 21662516 EAN 3800170252271 VT-6147

Related products (SKUs): 6624, 6625, 6626, 216625, 216626, 2166251, 2166256, 2166261

Product description

- Modern SMD-CREE LED technology ensuring high reliability and durability
- 6-year warranty
- Ultra Thin, modern and elegant design
- High luminous efficiency of 110Lm/W
- The luminaire is easy to install on the surface without the use of additional accessories or frames
- Can be hung using ropes available separately
- Separately packed, protected against damage
- No IR radiation, does not attract insects
- Does not contain lead or mercury
- Environmentally friendly
- Dimmable available on selected models or by using an accessory power supply
- Power 40W and luminous flux 4400lm
- Long life up to 50 000 hours
- Wide lighting angle 110° ensuring even light dispersion
- High color rendering index CRI 80+
- Switching frequency above 25 000 cycles
- Compact housing with dimensions 1195x295x30mm
- Possibility of surface and flush mounting
- Possibility of hanging using accessory V-TAC cables SKU 6018 (available separately)
- Solid and durable construction made of aluminum and PS
- AC input voltage 220—240V, 50/60Hz
- Power factor 0.9
- IP20 rating
- Operating temperature range from -20°C to +40°C
- Safe to use thanks to the built-in power supply and tight construction

GPSR Information

- Manufacturer: V-TAC Europe Ltd. Address: bul. "Rozhen" 41, 1271 Sofia, Bulgaria, office@v-tac.eu
- Importer: V-TAC Europe Ltd. Address: bul. "Rozhen" 41, 1271 Sofia, Bulgaria, office@v-tac.eu
- Distributor and importer in Poland: Led Europe Sp. z o.o. Address: ul. Starorudzka 12E 93-491 Łódź, Poland, biuro@led-europe.pl
- Documents confirming compliance of products with applicable safety standards are available on the website www.v-tac.eu. If the required documentation is not available, please contact the local distributor: biuro@led-europe.pl
- If you have any problems with the product, contact the distributor in Poland: biuro@led-europe.pl
- Country of production: China