







**12W LED dome light with sensor with CREE CHIP 4000K white body**

SKU 218086 EAN 3800170252240 VT-13

Related products (SKUs): 807, 808, 809, 21808, 21809



## TECHNICAL SPECIFICATION

Power	12W	Lifetime	25000h	Rated load	12W(24pcs LED)
Equivalent power	100W	Input voltage	200-240V	Ambient light	<3-2000LUX Adjustable
Luminous flux (lm)	900 lm	Frequency	50/60Hz	Ignition time (100%)	0.001s
Light color	Neutral white	Power factor	>0,5	On/Off cycles	>20000
Color temperature	4000K	CRI	80+	Operating conditions	-20° +45°
Beam angle	200°	Material	Plastic	Size	290x60mm
Voltage	230V	Housing color	White	Mounting size	290x60mm
SKU	SKU 218086	Type	Ceiling	Product weight	0,83
EAN barcode	3800170252240	Dimming	NIE	Volume	0,006543
Product code	VT-13	IP rating	IP20	Pack length	295mm
Series	Ceiling lights with sensor	Sensor type	Infrared	Pack width	64mm
Energy class	F	Detection range	360°	Pack height	295mm
Base	Integrated LED fixture	Detection distance	6m	Master carton	10
Shape	Round	Detection speed	0,6-1,5m/s	Brand	V-TAC
LED module type	CREE LED	Delay	Min. 10s+/-3s. Max. 3min+/-30min	Warranty	6y

## TECHNICAL SPECIFICATION

Page 2/2

Certifications	CE, EMC, ROHS
Efficacy (lm/W)	75 lm/W
Parameters	Motion sensor
ETIM	EC002892
CN code	8539 51 00
EPREL	2417027

**12W LED dome light with sensor with CREE CHIP 4000K white body**

SKU 218086    EAN 3800170252240    VT-13

Related products (SKUs): 807, 808, 809, 21808, 21809

## Product description

- LED ceiling fixture with a built-in PIR motion sensor
- The SMD-CREE chip technology used ensures high reliability and durability
- 6-year warranty
- A new generation of luminaires with CREE chip technology ensuring high reliability
- CREE LED is a world leader in LED technology with over 35 years of experience 1800 patents and exceptional performance, durability and precision
- Power 12W and luminous flux 1000 lumens
- Light color 4000K
- Built-in power supply for simple installation
- Detection range up to 6 meters
- Detection angle 360°
- Adjustable lighting time from 10 seconds to 3 minutes
- Adjustable daylight sensitivity from 3 to 2000 lux
- Recommended installation height from 2.2 to 4 meters
- IP20 protection rating intended for indoor use only
- Durability up to 25 000 hours
- Fixture dimensions 290x59.5mm

## GPSR Information

- Manufacturer: V-TAC Europe Ltd. Address: bul. "Rozhen" 41, 1271 Sofia, Bulgaria, office@v-tac.eu
- Importer: V-TAC Europe Ltd. Address: bul. "Rozhen" 41, 1271 Sofia, Bulgaria, office@v-tac.eu
- Distributor and importer in Poland: Led Europe Sp. z o.o. Address: ul. Starorudzka 12E 93-491 Łódź, Poland, biuro@led-europe.pl
- Documents confirming compliance of products with applicable safety standards are available on the website [www.v-tac.eu](http://www.v-tac.eu). If the required documentation is not available, please contact the local distributor: [biuro@led-europe.pl](mailto:biuro@led-europe.pl)
- If you have any problems with the product, contact the distributor in Poland: [biuro@led-europe.pl](mailto:biuro@led-europe.pl)
- Country of production: China