








**192 14W LED strip light with CREE CHIP 3in1 IP20 24V 8mm double pcb**

SKU 240836 EAN 3800170253568 VT-2835 192

Related products (SKUs): ---



**TECHNICAL SPECIFICATION**

Power	14W	CRI	90+	Master carton	300
Luminous flux (lm)	1425 lm	Material	PCB	Brand	V-TAC
Light color	CCT tunable white	Type	192LED/m	Warranty	6y
Color temperature	3000K - 6500K	Dimming	TAK	Certifications	CE, EMC, ROHS
Beam angle	120°	IP rating	IP20	Efficacy (lm/W)	100 lm/W
Voltage	24V	Cut point	Cut every 12 LEDs	Parameters	Power and luminous flux are given for 1m of product
SKU	SKU 240836	Ignition time (100%)	0.001s	ETIM	EC001959
EAN barcode	3800170253568	On/Off cycles	>20000	CN code	8539 52 00
Product code	VT-2835 192	Operating conditions	-20° +45°	EPREL	2407757
Series	LED strips	Length	10m		
Energy class	F	Width	8mm		
Shape	LED strip	Product weight	0,3		
LED module type	CREE LED	Volume	0,000059		
Lifetime	25000h	Pack length	157mm		
Input voltage	DC:24V	Pack width	15mm		
Number of LEDs	192LED/m	Pack height	167mm		

**192 14W LED strip light with CREE CHIP 3in1 IP20 24V 8mm double pcb**

SKU 240836

EAN 3800170253568

VT-2835 192

Related products (SKUs): ---

## Product description

• The V-TAC CREE LED strip has a 6 year warranty and uses high-performance SMD 2835 diodes from CREE, which ensures exceptional light efficiency and long life. The product is characterized by a very high color rendering index CRI above 90, thanks to which the colors of the environment look natural and are faithfully reproduced. The key feature is the width of the strip, which is approximately 8mm, which allows its installation in typical aluminum profiles and furniture installations. The tape generates a very high luminous flux of 1425 lumens per meter with a power consumption of 15W per meter, offering a strong and even line of light. The density of 192 diodes per meter eliminates the effect of light points, ensuring a full, uniform line. The 24V DC power supply guarantees stable operation and minimal voltage drop even over long distances. The flexible design allows you to easily cut the tape in designated places and adapt it to complex lighting designs. The product supports CCT 3in1 color regulation, which allows you to obtain a wide range of light temperatures depending on the controller used.

## GPSR Information

- Manufacturer: V-TAC Europe Ltd. Address: bul. "Rozhen" 41, 1271 Sofia, Bulgaria, office@v-tac.eu
- Importer: V-TAC Europe Ltd. Address: bul. "Rozhen" 41, 1271 Sofia, Bulgaria, office@v-tac.eu
- Distributor and importer in Poland: Led Europe Sp. z o.o. Address: ul. Starorudzka 12E 93-491 Łódź, Poland, biuro@led-europe.pl
- Documents confirming compliance of products with applicable safety standards are available on the website [www.v-tac.eu](http://www.v-tac.eu). If the required documentation is not available, please contact the local distributor: [biuro@led-europe.pl](mailto:biuro@led-europe.pl)
- If you have any problems with the product, contact the distributor in Poland: [biuro@led-europe.pl](mailto:biuro@led-europe.pl)
- Country of production: China