






2W emergency exit light wall/ceiling 12 hours charging CREE CHIP 6000K

SKU 836-6 EAN 3800170256576 VT-519-S

Related products (SKUs): ---



TECHNICAL SPECIFICATION

Power	2W	Number of LEDs	16	Volume	0,00436
Luminous flux (lm)	120 lm	CRI	80+	Pack length	315 mm
Light color	Cool white	Material	Plastic	Pack width	45 mm
Color temperature	6000K	Housing color	White, green	Pack height	245 mm
Voltage	230V	Dimming	NIE	Master carton	10
SKU	SKU 836-6	IP rating	IP20	Brand	V-TAC
EAN barcode	3800170256576	Charging time	12h	Warranty	3y
Product code	VT-519-S	Operating time	>3h	Certifications	CE, EMC, ROHS
Base	Integrated LED fixture	Battery capacity	Ni-cd 3.6V, 900mAh	Efficacy (lm/W)	60 lm/W
Shape	Rectangle	Detection distance	24m - both sides	Additional information	Self-adhesive labels; indicator LED
LED module type	CREE LED	Delay	24m - both sides	Parameters	Ceiling surface-mounted
Input voltage	AC:220-240V, 50/60Hz	Ignition time (100%)	0.001s	ETIM	EC000481
Discharge current (emergency mode)	200-280mA	Color consistency	<6	CN code	8539 51 00
Charging current	100-140mA	Operating conditions	-20° +45°		
Frequency	50/60Hz	Size	310x230x35mm		
Power factor	>0,5	Product weight	1,09		



**2W emergency exit light wall/ceiling 12 hours charging CREE
CHIP 6000K**

SKU 836-6 EAN 3800170256576 VT-519-S

Related products (SKUs): ---

Product description

- The fixtures do not have the CNBOP certificate
- 3-year warranty
- A new generation of luminaires with CREE chip technology, ensuring high reliability
- CREE LED is a global leader in LED technology with over 35 years of experience, 1800 patents, and exceptional performance, durability and precision
- Built-in efficient CREE LED chips with low power consumption — only 2W
- Reliable Ni-Cd battery designed for long life and low maintenance requirements
- Visibility distance up to 30 meters on both sides
- Maintained emergency operation function (continuous operation also with the current supply voltage)
- Backup time in emergency mode up to 3 hours
- Green LED indicator indicating correct operation
- Test button to quickly check the system status
- The set contains 4 various pictograms (legends) to adjust the evacuation direction

GPSR Information

- Manufacturer: V-TAC Europe Ltd. Address: bul. "Rozhen" 41, 1271 Sofia, Bulgaria, office@v-tac.eu
- Importer: V-TAC Europe Ltd. Address: bul. "Rozhen" 41, 1271 Sofia, Bulgaria, office@v-tac.eu
- Distributor and importer in Poland: Led Europe Sp. z o.o. Address: ul. Starorudzka 12E 93-491 Łódź, Poland, biuro@led-europe.pl
- Documents confirming compliance of products with applicable safety standards are available on the website www.v-tac.eu. If the required documentation is not available, please contact the local distributor: biuro@led-europe.pl
- If you have any problems with the product, contact the distributor in Poland: biuro@led-europe.pl
- Country of production: China