



2W LED wall surface emergency exit light 6000K

SKU 836 EAN 3800157641357 VT-519-S-12

Related products (SKUs): ---


TECHNICAL SPECIFICATION

Power	2W	Material	Plastic	Pack width	45mm
Luminous flux (lm)	140 lm	Housing color	White, green	Pack height	245mm
Light color	Cool white	Dimming	NIE	Master carton	10
Color temperature	6000K	IP rating	IP20	Brand	V-TAC
Voltage	230V	Charging time	12h	Warranty	3y
SKU	SKU 836	Operating time	>3h	Certifications	CE, EMC, ROHS
EAN barcode	3800157641357	Battery capacity	Ni-cd 3.6V, 900mAh	Efficacy (lm/W)	70 lm/W
Product code	VT-519-S-12	Detection distance	24m - both sides	Additional information	Self-adhesive labels; indicator LED
Base	Integrated LED fixture	Delay	24m - both sides	Parameters	Ceiling surface-mounted
LED module type	SAMSUNG	Ignition time (100%)	0.001s	ETIM	EC000481
Input voltage	220-240V	Color consistency	<6	CN code	8539 51 00
Discharge current (emergency mode)	200-280mA	Operating conditions	-20° +45°		
Charging current	100-140mA	Size	380x51x195mm		
Frequency	50/60Hz	Product weight	1,1		
Power factor	>0,5	Volume	0,003693375		
CRI	80+	Pack length	335mm		

**2W LED wall surface emergency exit light 6000K**

SKU 836 EAN 3800157641357 VT-519-S-12

Related products (SKUs): ---

Product description

- The lighting fixtures do not have the CNBOP certificate

GPSR Information

- Manufacturer: V-TAC Europe Ltd. Address: bul. "Rozhen" 41, 1271 Sofia, Bulgaria, office@v-tac.eu
- Importer: V-TAC Europe Ltd. Address: bul. "Rozhen" 41, 1271 Sofia, Bulgaria, office@v-tac.eu
- Distributor and importer in Poland: Led Europe Sp. z o.o. Address: ul. Starorudzka 12E 93-491 Łódź, Poland, biuro@led-europe.pl
- Documents confirming compliance of products with applicable safety standards are available on the website www.v-tac.eu. If the required documentation is not available, please contact the local distributor: biuro@led-europe.pl
- If you have any problems with the product, contact the distributor in Poland: biuro@led-europe.pl
- Country of production: China